



# OLED MODULES



**Features:**

- High Contrast
- High Brightness
- Wide View Angle

**OLED Character- AL Series**

Compatible with LCD PINS; High Contrast > 10,000:1; Operation Temp.: -40 to 85°C

Number of Pixels	Model Construction	Module Size (mm)	Viewing Area (mm)	Interface
8 x 2	COG+Board	58 x 32 x 9.7	29.81 x 13.5	Parallel/Serial
16 x 1	COG+Board	80 x 36 x 9.7	61.56 x 8.56	Parallel/Serial
16 x 2	COG+Board	80 x 36 x 9.7	58.22 x 13.52	Parallel/Serial
16 x 4	COG+Board	87 x 60 x 9.7	58.2 x 22.8	Parallel/Serial
20 x 2	COG+Board	116 x 37 x 9.7	75.52 x 13.52	Parallel/Serial
20 x 4	COG+Board	98 x 60 x 9.7	72.42 x 22.82	Parallel/Serial
40 x 2	COG+Board	182 x 33.5 x 9.7	149.7 x 13.5	Parallel/Serial

**OLED Graphic- SO Series**

Number of Pixels	Model Construction	Module Size (mm)	Viewing Area (mm)	Interface
128 x 64	COG+Board	75.0 x 52.7 x 8.0	57.0 x 29.4	Parallel/Serial



# OLED DISPLAY



**OLED DISPLAY**

Size	Number of Pixels	Model Construction	Dimensions (mm)	Active Area (mm)	Interface
0.95"	96x64	COG+FPC	25.76x52.18	20.14x13.42	Parallel / Serial
1.1"	96x96	COG+FPC	25.77x56.15	19.85x19.86	Parallel / Serial
1.5"	128x128	COG+FPC	33.8x68.14	26.79x26.86	Parallel / Serial
1.8"	160x128	COF	42.7x33.4	35.015x28.012	Parallel / Serial

